

DS-D5022QE-B 22" LED Monitor

key Features

- LED backlit technology with full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Multiply inputs: HDMI, VGA
- 3D comb filter, 3D De-interlace
- 3D noise reduction
- VESA stand bracket

Model:

DS-D5022QE-B



DS-D5022QE-B 22" LED Monitor



Specification

Model	DS-D5022QE-B
Display	
Display Type	LED-Backlit
Screen Size	22"
Pixel Pitch(H×V)	0.247mm ×0.247mm
Max Resolution	1920×1080
Brightness	250cd/m2 (Typical)
Contrast	1000:1
Response Time	5ms
Color	16.7M
Viewing Angle	Horizontal 170°, Vertical 160°
Interface	
HDMI	1
VGA	1
Mounting	
VESA	100mm × 100mm
General	
Power Supply	100 ~ 240V AC
Consumption	< 30W(on) < 0.5W(Standby)
Operation Temperature	0°C ~ 40 °C
Operating Humidity	10%~85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5%~95% (No Condensation)
Dimension (W×H×D)	511.4x313.0x45.4 (mm) 20.1x12.3x1.8(inch)
Weight	4.4Kg(Gross weight) , 3.2(Net weight)